



2/3" 1.4/16mm C		1/2"	1/3"	
FOCAL LENGTH		f=16mm		
MAX. DIAMETER (RATIO)		F=1:1.4~16		
ELEMENT		6 Elements in 6 Groups		
PICTURE SIZE		6.6x8.8mm	4.8x6.4	3.6x4.8
ANGLE	VER. ANGLE	22.8°	16.6°	12.4°
	HOR. ANGLE	30.5°	22.2°	16.6°
	DIA. ANGLE	38.3°	27.7°	20.8°
DISTORTION		-15%	-0.8%	-0.4%
SHOOTING RANGE AT	VER.	82.6mm	59.6mm	44.5mm
MINIMUM FOCUS	HOR.	111.8mm	80.1mm	59.6mm
DISTANCE	DIA.	142.5mm	101.1mm	74.9mm
MINIMUM FOCUS DISTANCE		0.1m	0.2m	光学保証範囲
FLANGE BACK		17.526	mm	in air
BACK FOCUS		12.15mm	in air	
FILTER SCREW SIZE		M27x0.5		
FRONT/REAR EFFECTIVE DIA.		Front: Ø 12.0mm	Rear: Ø 12.8mm	
MOUNT		C-MOUNT		
EXIT PUPIL		-48.9mm		
TEMPERATURE RANGE		-10~+45° C		
STORAGE TEMPERATURE RANGE		-40~+60° C		
RESOLUTION CENTER/CORNER		Center 100line/mm	Corner 60line/mm	
WEIGHT		55g		

注) 本仕様書については、予告なしに変更する場合があります。



		尺 度	1/1	承 認	製 図
		機 種 名	LM16JC		
		機 種 番	2/3" 1.4/16mm		
05.6.23	作成年月日				