



| 2/3" 1.4/16mm C | | 1/2" | 1/3" |
|---------------------------|------------|---------------------------------|---------|
| FOCAL LENGTH | | f=16mm | |
| MAX. DIAMETER (RATIO) | | F=1:1.4~16 | |
| ELEMENT | | 7 groups 8 elements | |
| PICTURE SIZE | | 6.6x8.8mm | 4.8x6.4 |
| ANGLE | VER. ANGLE | 22.7° | 16.4° |
| | HOR. ANGLE | 30.0° | 21.8° |
| | DIA. ANGLE | 37.0° | 27.0° |
| DISTORTION (TV) | | -0.05% | - |
| SHOOTING RANGE AT | VER. | 84.4mm | 61.2 |
| MINIMUM FOCUS | HOR. | 112.8mm | 81.8 |
| DISTANCE | DIA. | 141.2mm | 102.5 |
| MINIMUM FOCUS DISTANCE | | 0.2m | |
| FLANGE BACK | | 17.526 mm in air | |
| BACK FOCUS | | 13.1mm in air | |
| FILTER SCREW SIZE | | M27x0.5 | |
| FRONT/REAR EFFECTIVE DIA. | | Front Ø 20.2mm Rear Ø 15.5mm | |
| MOUNT | | C-MOUNT | |
| EXIT PUPIL | | 340mm | |
| TEMPERATURE RANGE | | -10~+45° C | |
| STORAGE TEMPERATURE RANGE | | -40~+60° C | |
| RESOLUTION CENTER/CORNER | | Center 120lp/mm Corner 100lp/mm | |
| WEIGHT | | 81g | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | | |
|---------|--------|-----|--------|----|------------------|----|
| | 尺 度 | 1/1 | 承 認 | 杉田 | 製 図 | 八木 |
| | | | | | 2/3" F1.4 f=16mm | |
| 07.7.19 | | | | | LM16JC1MS | |
| | | | | | 作成年月日 | |