



2/3" 1.4/8mm C		1/2"	1/3"
FOCAL LENGTH		f=8mm	
MAX. DIAMETER (RATIO)		F=1:1.4,4,8,16	
PICTURE SIZE		6.6x8.8mm	4.8x6.4
ANGLE	VER. ANGLE	43.9°	32.5°
	HOR. ANGLE	56.5°	42.6°
	DIA. ANGLE	67.0°	52.1°
DISTORTION (TV)		-0.6%	-0.3%
WORKING DISTANCE	500mm	0.016x	
	400mm	0.020x	
	300mm	0.027x	
	200mm	0.039x	
MAGNIFICATION	200mm	0.039x	
	100mm	0.075x	
MINIMUM FOCUS DISTANCE		0.1m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		9.74mm in air (Mechanical 9.1mm in air)	
FILTER SCREW SIZE		M27x0.5	
FRONT/REAR EFFECTIVE DIA.		前φ17.5mm	後φ15.6mm
MOUNT		C-MOUNT	
EXIT PUPIL		225.6mm	
TEMPERATURE RANGE		-10~+50°C	
STORAGE TEMPERATURE RANGE		-20~+60°C	
RESOLUTION CENTER/CORNER		中心100本/mm	周辺80本/mm
WEIGHT		g	

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。

		尺度	1/1	承認	入木	製図	入木
		機種名	2/3" F1.4 f=8mm				
2014.2.25	作成年月日						