



φ23 2.8/8.5mm C	
FOCAL LENGTH	f=8.5mm
MAX. DIAMETER (RATIO)	F=1:2.8~22
ELEMENT	14 GROUPS 17 ELEMENTS
PICTURE SIZE	13.8x18.4mm
ANGLE	VER. ANGLE 77.1° HOR. ANGLE 93.5° DIA. ANGLE 106.0°
DISTORTION (TV)	0.12% (WD=300mm)
SHOOTING RANGE AT	VER. 179mm
MINIMUM FOCUS	HOR. 239mm
DISTANCE	DIA. 298m
MINIMUM FOCUS DISTANCE	0.1m
FLANGE BACK	17.526mm in air
BACK FOCUS	12.9mm in air
FILTER SCREW SIZE	M72x075
FRONT/REAR EFFECTIVE DIA.	FRONT φ45.5mm REAR φ16.5mm
MOUNT	C-MOUNT
EXIT PUPIL	-75.1mm
TEMPERATURE RANGE	-10~+50° C
STORAGE TEMPERATURE RANGE	-20~+60° C
RESOLUTION CENTER/CORNER	Center 160lp/mm Corner 80lp/mm
LENS COATING	WIDE BAND MULTI COATING
WEIGHT	245g

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



	尺度 1/1	承認 八木	製図 大口
	φ23 F2.8 f=8.5mm		
2013.4.15	作成年月日		
	LM8XC		