

Nuvo-9531 Series

Intel® 12th -Gen Core™ i9/ i7/ i5/ i3 Compact Fanless Computer with 4x 2.5GbE, 4x USB3.2 and 1x Hot-swappable HDD Tray



CE FC

Key Features

- 212 x 165 x 63 mm low-profile design
- Intel® 12th-Gen Core™ 35W/ 65W LGA1700 CPU
- Rugged, -25°C to 60°C fanless operation
- 4x 2.5GbE with optional PoE+ and 4x USB3.2 Gen 1 with screw-lock
- M.2 2280 Gen4x4 NVMe and 1x hot-swappable HDD tray for storage
- 4-CH isolated DI and 4-CH isolated DO
- VGA + DP dual display outputs
- Optional ignition power control

Preliminary

Contact Neosys

Get Quote

Introduction

Nuvo-9531 is one of the most compact fanless embedded computers based on the Intel® 12th -Gen Alder Lake platform. Measuring just 212 x 165 x 63 mm, it can fit into restricted spaces, such as in robotic arm and AMR applications. Despite its compact size, Nuvo-9531 does not compromise on performance. Built on the advanced Intel 7 process, Intel® 12th-Gen processors have up to 16 cores/ 24 threads to deliver up to 1.8x the performance when compared to previous Intel 10th or 11th Gen platforms. Nuvo-9531 is a compact fanless embedded computer that offers the ultimate computing for various industrial applications.

Nuvo-9531 has rich I/O functions. It features four 2.5GbE with optional PoE+ PSE and four USB3.2 Gen1 ports for multiple camera connectivity for machine vision and surveillance applications. In addition, it features a M.2 Gen4x4 slot for the latest NVMe SSDs that support read/ write speeds up to 7000 MB/s; a hot-swappable HDD tray to hot-swap the storage drive without turning off the system or dismantling the chassis; two mPCIe and one M.2 E key slots to install WiFi or 5G/ 4G wireless communication modules. The system is also equipped with 8x DIO, 2x COM ports, and dual display outputs for your industrial embedded application needs.

As a compact embedded computer, Nuvo-9531 delivers excellent computing performance and offers an abundance of I/O connections. It is suitable for a variety of industrial applications, especially when installation space is limited.


Specifications

| System Core | | Internal Expansion Bus | |
|----------------------------------|--|--------------------------|---|
| Processor | Support Intel® 12th-Gen Alder Lake Core™ CPU (LGA1700 socket, 35W/ 65W TDP) | Mini PCI Express | 2x full-size mini PCI Express sockets with internal SIM sockets |
| | - Intel® Core™ i9-12900E/ i9-12900TE | M.2 E key | 1x M.2 2230 E key socket for WiFi5, WiFi6 or Google edge TPU module |
| | - Intel® Core™ i7-12700E/ i7-12700TE | Storage Interface | |
| | - Intel® Core™ i5-12500E/ i5-12500TE | SATA HDD | 1x hot-swappable 2.5" HDD/ SSD tray for 7mm HDD/ SSD |
| | - Intel® Core™ i3-12100E/ i3-12100TE | M.2 | 1x M.2 2280 M key socket (PCIe Gen4 x4) for NVMe SSD |
| | - Intel® Pentium® G7400E/ G7400TE | Power Supply | |
| | - Intel® Celeron® G6900E/ G6900TE | DC Input | 1x 3-pin pluggable terminal block for 8 to 48V DC input with optional ignition power control |
| Chipset | Intel® H610E platform controller hub | Mechanical | |
| Graphics | Integrated Intel® UHD Graphics 770 (32EU) | Dimension | 212mm (W) x 165 mm (D) x 63 mm (H) |
| Memory | Up to 32GB non-ECC DDR4 3200 SDRAM (one SODIMM slot) | Weight | 2.5 kg |
| TPM | Supports dTPM 2.0 | Mounting | Wall-mount (standard) or DIN-rail mount (optional) |
| I/O Interface | | Environmental | |
| Ethernet | 4x 2.5GBASE-T Ethernet ports by Intel® I226-IT GbE controllers | Operating Temperature | with 35W CPU -25°C ~ 60°C * with 65W CPU (installation of the optional fan kit is recommended) -25°C ~ 60°C ** |
| PoE+ | Optional IEEE 802.3at PoE+ PSE for 4x2.5GbE ports 100 W total power budget | Storage Temperature | -40°C ~ 85°C |
| USB 3.2 | 4x USB 3.2 Gen1 (5 Gbps) ports | Humidity | 10%~90% , non-condensing |
| USB 2.0 | 2x USB 2.0 ports | Vibration | Operating, MIL-STD-810G, Method 514.6, Category 4 |
| Video Port (Integrated Graphics) | 1x VGA output, supporting 1920 x 1200 resolution 1x DisplayPort, supporting 4096 x 2304 resolution | Shock | Operating, MIL-STD-810G, Method 516.6, Procedure I, Table 516.6-II |
| Serial Port | 1x software-programmable RS-232/422/485 ports (COM1) 3x 3-wire RS-232 ports (COM2/3/4) or 1x RS-422/485 port (COM2) | EMC | CE/FCC Class A, according to EN 55032 & EN 55035 |
| Audio | 1x 3.5 mm jack for mic-in and speaker-out | | |
| Isolated DIO | 4-CH isolated DI and 4-CH isolated DO | | |


* For sub-zero operating temperature, a wide temperature HDD or Solid State Disk (SSD) is required.

** For 65W CPUs, the optional fan kit is recommended for operating at ambient temperatures higher than 50°C.

Appearance



Dimensions



Ordering Information

| Model No. | Product Description |
|------------------|--|
| Nuvo-9531 | Intel® 12th-Gen Core™ i9/ i7/ i5/ i3 compact fanless computer with 4x 2.5GbE, 4x USB3.2 Gen 1 and a hot-swappable HDD tray |
| | <i>Optional 802.3at PoE+ PSE for 4x 2.5GbE ports</i> |
| | <i>Optional ignition power control</i> |

Optional Accessories

| | |
|--------------------|--|
| PA-160W-OW | 160W AC-DC power adapter 20V/8A; 18AWG/120cm; cord end terminals for terminal block, operating temperature: -30°C to 70°C. |
| PA-280W-ET2 | 280W AC/DC power adapter 24V/11.67A; 16AWG/ 100cm; cord end terminals for terminal block, operating temperature : -30°C to 60°C. (recommended for 65W CPU) |
| DINRAIL-31 | DIN-rail mounting assembly for Nuvo-9531 series |
| Fan kit | Fan kit with 92mm x 92mm fan for Nuvo-9531 series |