



| 1" 1.4/12.5mm C | | 1" | 2/3" | 1/1.8" |
|---|------------|-----------------|-----------|----------------|
| FOCAL LENGTH | | f=12.5mm | | |
| F-NUMBER | | F=1:1.4,2.8,4,8 | | |
| PICTURE SIZE | | 9.6x12.8mm | 6.6x8.8mm | 5.4x7.2mm |
| ANGLE OF VIEW (∞) | VER. ANGLE | 42.5° | 29.5° | 24.2° |
| | HOR. ANGLE | 55.6° | 39.1° | 32.1° |
| | DIA. ANGLE | 67.6° | 48.3° | 39.9° |
| DISTORTION (TV) | | -1.58% | -1% | -0.6% |
| FIELD OF VIEW (MINIMUM FOCUS DISTANCE) | VER. | 243.5mm | 165.2mm | 134.6mm |
| | HOR. | 330.6mm | 222.4mm | 180.6mm |
| | DIA. | 420.6mm | 281.3mm | 227.7mm |
| MINIMUM FOCUS DISTANCE | | 0.3m | | |
| FLANGE BACK | | 17.526mm in air | | |
| BACK FOCUS | | 12.6mm in air | | |
| FILTER SCREW SIZE | | M35.5x0.5 | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ28.1mm | | REAR φ17.5mm |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | -45.9mm | | |
| TEMPERATURE RANGE | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | CENTER 120lp/mm | | CORNER 80lp/mm |
| WEIGHT | | 130g | | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|-------|-----|-----------------|------|---------|
| | | 尺度 | 1/1 | 工場番号 | HR976SR |
| | | 機種名 | F1.4/f12mm耐振レンズ | | |
| 2016.02.09 | 重量記載 | 機種番 | LM12HC-V | | |
| 2015.10.28 | 更新 | | | | |
| 2015.9.8 | 作成年月日 | | | | |