



2/3" 1.8/16mm C		1/2"	1/3"
FOCAL LENGTH		f=16mm	
MAX. DIAMETER (RATIO)		F=1:1.8~16	
ELEMENT		8 ELEMENTS 10 GROUPS	
PICTURE SIZE		6.6x8.8mm	4.8x6.4 3.6x4.8
ANGLE	VER. ANGLE	22.7°	16.6° 12.5°
	HOR. ANGLE	30.0°	22.0° 16.6°
	DIA. ANGLE	37.1°	27.4° 20.7°
DISTORTION (TV)		-0.20%	- -
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	45.7mm	33.1mm 24.8mm
	HOR.	61.1mm	44.3mm 33.1mm
	DIA.	76.5mm	55.5mm 41.5mm
MINIMUM FOCUS DISTANCE		0.1m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		14.6mm in air	
FILTER SCREW SIZE		M25.5x0.5	
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 21.2mm REAR ϕ 13.4mm	
MOUNT		C-MOUNT	
EXIT PUPIL		-53.6mm	
TEMPERATURE RANGE		-10~+50° C	
STORAGE TEMPERATURE RANGE		-20~+60° C	
RESOLUTION CENTER/CORNER		CENTER 200lp/mm CORNER 160lp/mm	
LENS COATING		WIDE BAND MULTI COATING	
WEIGHT		90 g	



		尺度 1/1	承認 八木	製図 八木
		機種名	2/3" F1.8 f=16mm	
		機種番	LM16JC10M	
09.09.01	作成年月日			