



Ø16 1.8/25mm C		
FOCAL LENGTH		f=25mm
MAX. DIAMETER (RATIO)		F=1:1.8~16
ELEMENT		6 GROUPS 8 ELEMENTS
PICTURE SIZE		12.8x9.6mm
ANGLE	VER. ANGLE	21.8°
	HOR. ANGLE	28.9°
	DIA. ANGLE	35.8°
DISTORTION (TV)		-0.34%
SHOOTING RANGE AT	VER.	64mm
	HOR.	86mm
	DIA.	108mm
MINIMUM FOCUS DISTANCE		0.15m
FLANGE BACK		17.526mm in air
BACK FOCUS		24.3mm in air
FILTER SCREW SIZE		M34x0.5
FRONT/REAR EFFECTIVE DIA.		FRONT Ø27mm REAR Ø18.2mm
MOUNT		C-MOUNT
EXIT PUPIL		-63.9mm
TEMPERATURE RANGE		-10~+50° C
STORAGE TEMPERATURE RANGE		-20~+60° C
RESOLUTION CENTER/CORNER		CENTER 160L/mm CORNER 120L/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		g

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺 度	1/1	承 認	入木	製 図	大口
		LM25SC					
		1" F1.8 f=25mm					
2013.05.10	作成年月日						