



| | | 1.1" | 2.5/6.5mm C | 1.1" | 1" | 2/3" |
|---|------------|-----------------|-------------|-----------------|----|-----------|
| FOCAL LENGTH | | f=6.5mm | | | | |
| F-NUMBER | | F=2.5-16 | | | | |
| PICTURE SIZE | | 10.6x14.1mm | | 9.6x12.8mm | | 6.6x8.8mm |
| ANGLE OF VIEW (∞) | VER. ANGLE | 78.7° | | 73.0° | | 53.5° |
| | HOR. ANGLE | 95.7° | | 89.9° | | 68.1° |
| | DIA. ANGLE | 109.1° | | 103.4° | | 80.8° |
| DISTORTION (TV) | | -1.51% | | -1.27% | | -0.68% |
| FIELD OF VIEW (MINIMUM FOCUS DISTANCE) | VER. | 190mm | | 172mm | | 117mm |
| | HOR. | 256mm | | 231mm | | 157mm |
| | DIA. | 323mm | | 292mm | | 197mm |
| MINIMUM FOCUS DISTANCE | | 0.1m | | | | |
| FLANGE BACK | | 17.526mm in air | | | | |
| BACK FOCUS | | 10.9mm in air | | | | |
| FILTER SCREW SIZE | | M82x0.75 | | | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ46.0mm | | REAR φ18.5mm | | |
| MOUNT | | C-MOUNT | | | | |
| EXIT PUPIL | | -61.7mm | | | | |
| TEMPERATURE RANGE | | -10~+50°C | | | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | | | |
| RESOLUTION CENTER/CORNER | | CENTER 160lp/mm | | CORNER 100lp/mm | | |
| WEIGHT | | TBD | | | | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|-------|-----|-----------|---------|-------|
| | | 尺度 | 1/1 | 工場番号 | LM6FC |
| | | 機種名 | 1.1" F2.5 | f=6.5mm | |
| | | 機種番 | LM6FC 外観図 | | |
| 2018.04.05 | 作成年月日 | | | | |